

bio-gel⁺

PRO KLEEN[®] MOP WATER ADDITIVE

ADVANCED FORMULA | SUPERIOR CLEANING

Biologically enhanced cleaning formula to naturally remove organic debris

-  Bio-Enzymatic Action Eliminates Organic Build-Ups
-  Digests Organic Waste, Grease & Food By-Products
-  Non-Pathogenic & Eliminates Odors
-  Reduces the Risk of Slips and Falls
-  Deodorizes with a Clean Fresh Scent
-  Leaves Floors Clean

Tripple
Action
Cleaning
Power



INSTRUCTIONS FOR USE

Refer to full label for additional instructions for use.
Shake well before using.

For use in and around Commercial, Industrial, Medical and Residential buildings such as: garages, schools, meat packing facilities, food processing facilities, nursing homes, mortuaries, offices, supermarkets, restaurants, convenience stores, apartment complexes, transportation terminals, boat/ships, and many more facilities. Can be used in and around food and non-food areas such as: dumpsters, drain lines, scuppers, outside drains, statuaries, compactors, overflow lines, grease traps, loading docks, rendering vats, elevator pits, lift stations, trough drains, vault toilets, showers, ceramic tile floors, and many more areas.

Surface Area Treatment: BIO-GEL[®] is designed to be tank mixed for direct application to floors and other surface areas, dumpsters, trash receptacles, dumb waiters, trash chutes, trough vats, and statuaries. Mix at a rate of 4-8 ounces of BIO-GEL[®] per gallon and apply with a LOW-PRESSURE hand sprayer, power sprayer or mop bucket. Completely cover the target area. DO NOT PERMIT TRAFFIC ON THE TREATED AREA UNTIL COMPLETELY DRY.

Drains: For best results, flush drain with 2-gallons of warm water. BIO-GEL[®] should be applied at the end of the workday or any other time when the drain will be inactive. Drains with heavy organic build-up should be scrubbed or steamed out to remove heavy debris prior to initial application.

Initial Treatment: Depending on conditions, apply 2-8 ounces of BIO-GEL[®] per drain to establish adequate bacterial colonies throughout the drain line. Using a spray nozzle or quart container pouring cap, liberally coat the surrounding areas including grout expansion joints and grade plates. Be certain to coat the interior circumference of the drain.

General Maintenance: Apply 2-4 ounces of BIO-GEL[®] per drain, per week.

Foam: Mix 1:1 BIO-GEL[®] to water. A foaming sprayer is required. For additional foam thickness, increase the amount of BIO-GEL[®].

Repeat application as necessary.

PRECAUTIONARY STATEMENTS

KEEP OUT OF THE REACH OF CHILDREN AND PETS!
MAY BE HARMFUL IF SWALLOWED.
IF SWALLOWED: Call 911 or Poison Control Center (800-222-1222).

MAY BE HARMFUL IF INHALED.
Do not inhale spray mist.
IF INHALED: Immediately remove person to fresh air. Call 911. If not breathing perform CPR.

PestWest USA LLC
7135 16th Street E, Suite 124
Sarasota, FL, 34243
office: 941.358.1983
fax: 941.358.1916
toll free: 866.476.7378
email: order@pestwest.com
www.pestwest.com

Net Contents:

5 US Gallons (640 fl.oz.)
Product Code: BIOGEL905 / 620-000006

MAY CAUSE MODERATE EYE IRRITATION.
IF IN EYES: Flush eyes with water for 20 minutes.
Call a physician if irritation persists.

Wash hands thoroughly with soap after handling.
Refer to the SDS for additional information.

STORAGE AND HANDLING: Store in a cool dry place.
Avoid direct contact with the sun.



5 055436 701576