# SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (modified by Regulation (EU) No. 453/2010)

SDS	Blacklight lamps
Supplier	Feilo Sylvania Germany GmbH
	Graf-Zeppelin-Straße 9
	91056 Erlangen
	Germany
Tradename	SPEK Lighting
General description	LAMP
Use	Fly attracting
Publicationdate	09.09.2014
General information	www.feilosylvania.com
Emergency phonenumber	+49 (0)9131-7930

# 2. Hazard identification

Not applicable to intact lamp. Lamp may crack when falling to the ground.

# 3. Composition/information on ingredients

Component	% by weight	CAS No.	EC No.	EC Classif	ination
Glass	>90		LO NO.	EC Classii	Ication
Strontium borate, europium-doped	<2	102110-29-2	310-028-8		
Krypton					
	<0,1	7439-90-9	231-098-5	GHS04	H280
Argon					OSHA-H01
Aigon	<0,1	7440-37-1	231-147-0	GHS04	H280
Mercury					OSHA-H01
iviercury	<0,1	7439-97-6	231-106-7	Repr. 1B	H360D
				GHS06	H330
				GHS08	H372
T				GHS09	H410
Tungsten	<0,1	7440-33-7	231-143-9		
Metals	<2		2011100		

4. First-aid measures	4.	First-aid	measures
-----------------------	----	-----------	----------

Capping cement

Skin	Apply pormal first aid for all and the		
Ingestion	Apply normal first aid for glass cuts if such occur through lamp breakage In the unlikely event of ingestion of a large quantity of material, seek medical		
Inhalation	attention		
	If discomfort, irritation or symptoms of pulmonary involvement develop, remove from exposure and seek medical attention		
Eyes	Wash eyes, including under eyelids, immediately with copious amounts of water for 15 minutes		
Remarks first aid	None		

#### 5. Fire fighting measures

Fire-extinguisher	Use extinguishing agents suitable for surrounding fire
Hazardous decomposition products in fire	silicon dioxide, aluminium oxides, mercury oxides, strontium oxide, boric oxides, europium oxides, metal oxide, tungsten oxides

#### 6. Accidental release measures

Spillage procedure	Not applicable if lamp is in original state. If lamps are broken: ventilate area where breakage occured. Clear up using special mercury vacuum cleaner or other appropriate agent for preventing vaporisation. Take standard measures for clearing up broken glass and deposit in a lockable container.
Emergency procedure	not applicable

# 7. Handling and storage

Local exhausting	Under normal circumstances not applicable	
Storage conditions	No special precautions	

Exposure limits : applicable to: Netherlands (20 °C; 1013	- L				
Glass	mb				
	+	No MAC(STEL) has been laid down			
Strontium borate, europium-doped	+	No MAC(STEL) has been laid down			
Krypton/Argon Mercury			STEL) has been laid down		
		TLV:	0.02 mg/m3 (Women in the fertile age: consult the industrial safety officer)		
Tungsten	Π	TLV:	5.8 mg/m3 (as inhalable dust)		
Metals	T	No MAC(S	STEL) has been laid down		
Capping cement		No MAC(S	STEL) has been laid down		
applicable to: Belgium (20 °C; 1013 mba	ar)				
Mercury	_	TLV:	0.025 mg/m3 S (Women in the fertile age: consult the industrial safe officer)		
Tungsten		TLV:	5 mg/m3		
Tungsten		STEL:	10 mg/m3		
applicable to: Germany (20 ºC; 1013 mb	ar)		1.590		
Mercury		TLV:	0.1 mg/m3 (Women in the fertile age: consult the industrial safety officer)		
Tungsten		TLV:	5 mg/m3 (as inhalable dust)		
applicable to: USA (25 °C; 1013 mbar)			o mg/mo (do minalable dust)		
Krypton/Argon		No MAC(STEL) has been laid down			
Mercury	S	TLV:	0.025 mg/m3 (Women in the fertile age: consult the industrial safety officer)		
Tungsten		TLV:	5 mg/m3		
Tungsten		STEL:	10 mg/m3		
C=Ceiling; S=Skin			To mg/mo		
Remarks exposure limits		none			
Odour threshold (20°C; 1013 mbar)		not traceab			
Advised personal protection		ot iraocab			
skin		not applical	ble		
eyes	_	not applicable			
inhalation		not applicable			
nstructions regarding broken lamps		аррпоа	010		
hese instructions only apply to broken lam	ns				
Ventilation		Use both general and local exhaust ventilation to maintain exposure levels below the Long or Short terms limits. If such ventilation is not available us the respirators as specified below.			
		tandard EN 149 must be followed whenever workplace conditions were the			
Eye protection		The use of safety glasses, goggles or face shields is recommended for handling			
Broken lamps, as described in European Standard EN 166			os, as described in European Standard FN 166		
Hygiene		Wear appropriate protective clothing to prevent skin exposure.  After handling broken lamps wash thoroughly before eating, handling tobacco products, applying cosmetics or using toilet facilities.			

Physical state	article
Colour	type dependent
Odour	odourless
Vapor rate/range	not applicable
Boiling point/range	not traceable
Melting point/range	> 480 °C
Flash point/range	not applicable
Explosive limits	not applicable
Dust explosions possible in air	not applicable
Density	not traceable
Vapour pressure	not applicable
Solubility in water	not applicable
Solubility in fat	not applicable
H	not applicable
Viscosity	not applicable
Autoignition temperature	
Decomposition temperature	not applicable
Electrostatic chargement	not traceable not traceable

10. Stability an	d reactivity		
	under conditions described	in section 7	
Conditions to a	void	none	
Reactions with	water	no	
Hazardous reac	tions	none	
Hazardous deco	omposition products at	none	
11. Toxicologic	al information		
Symptoms			
Skin	local	not applicable	
	general	not applicable	
Ingestion	local	not applicable	
	general	not applicable	
Inhalation	local	not applicable	
	general	not applicable	
Eyes	local	not applicable	
Romarko aumatan			

none not traceable

not traceable

Biological oxygen demand (5)		not traceable		
Chemical oxygen demand		not traceable	*	
Biological/chemical oxygen o	emand ratio	not traceable		
Degradability		not traceable		
Biochemical factor	Biochemical factor		Source	
Log Po/w		>2500 MERCURY 4.5 MERCURY		Supplier
Henry Constant Ecotoxicity :			Source	Chemicalcards
		not traceable		
Mercury	Fish	LC-50: 0.004 mg/l/96H	Source	Cumpliar
Mercury	Daphnia	EC-50: 0.0052 mg/l/48H	Source	Supplier
Mercury Algae Remarks on ecotoxicity		IC-50: 0.3 mg/l/72H		Supplier
		none	Source	Supplier

Remarks symptoms
Toxicity

Ames test

# 13. Disposal considerations

All fluorescent lamps contain some amount of mercury. All disposal options should be evaluated with respect to the requirements of the relevant local and national legislation. Before disposing of waste lamps check with state, country, and/or local officials for current guidelines and regulations.

14. Transport information	
ADR/RID	
UN-number	3506 MERCURY IN MANUFACTURING ARTICLES
Class	8 (6.1)
Packinggroup	
Transport emergency card	80GC9-III
The product contains less than 1kg of Mercur	ry and is therefore subject to SP366 and exempt from dangerous goods regulation.
IMO	estables to the obtained exempt from dangerous goods regulation.
UN-number	3506 MERCURY IN MANUFACTURING ARTICLES
Class	8 (6.1)
Packinggroup	
Marine pollutant	no
IATA/ICAO	
UN-number	3506 MERCURY IN MANUFACTURING ARTICLES
Class	8 (6.1)
Packinggroup	
The product contains less than 1g of Mercury	

The product contains less than 1g of Mercury and box contains less then 30g of mercury therefore goods are exempt from dangerous goods regulation

EC-Label	not applicable
Remarks on EC-labeling	none
16. Other information	
Remarks on SDS	Working of this product may release toxic dust.
	Toxic mercury vapours can be released if the lamp is broken.
	These lamps emit Ultraviolet Radiation (UV-A). Avoid prolonged exposure
	For transport exemption consult applicable regulations.
	The product contains <= 10 mg mercury.
Inner company references	none
Overview relevant H-sentences from	n all components in section 3
H330	Fatal if inhaled
H372	Causes damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects
H360D	May damage fertility or the unborn child
H280	If under pressure, may explode if heated
OSHA-H01	May displace oxygen and cause rapid suffocation
Date last update	10.11.2016

The information provided in this Safety Data Sheet is correct to the best of the knowledge, information and belief of Feilo Sylvania Germany at the date of its printing.