# **AMERIVAP® SYSTEMS**

The Leader in Dry Steam Vapor Sanitizing Technology





AmeriVap's innovative thinking keeps creating new ways to put super-heated dry steam vapor to work for our growing list of commercial customers and applications. Our steam cleaning systems bring new levels of efficiency to cleaning and sanitizing all kinds of surfaces and spaces, removing residues and restoring appearances.

Our dry steam vapor sanitizing technology cuts the cost and time of cleaning and helps to conserve precious natural resources; all while eliminating toxic or unsanitary waste and fumes. In one movement, superheated dry steam vapor dissolves and dries the surface instantly. With the AmeriVap® dry steam cleaning system you can be confident that you and your employees are following safe and effective sanitation procedures.

#### STANDARD ATTACHMENTS

- 1 Rectangular Brush
- 1 Triangular Brush with Elbow
- 2 1" Nylon Detail Brush
- 2 1" Bronze Detail Brush
- 2 1" Stainless Steel Detail Brush
- 1 2.5" Circular Nylon Brush
- 1 2.5" Circular Bronze Brush
- 1 "Turbo" Nozzle (round opening) Gray
- 1 Standard Nozzle (cross cut) Red/Black
- 2 Extension Tubes, 19"
- 1 Flexible Hose, 10'
- 1 Blitz Pad Set with Holder
- 1 Window Squeegee
- 1 Filler Bottle, Non-Spill
- 6\* 32 oz.,100% Cotton Terry Cloth Towels
  \*3 Towels standard with the Steamax
- 1 Cord Winder, Automatic Recoil
- 1 Instructional/Demo Video
- 1 User's Guide

### **OPTIONAL ATTACHMENTS**

- · Diamond Brush with Elbow
- Wall Attachment for Rectangular Brush
- Red Cross Nozzle (color code specific jobs)
- 2.5" Bronze and 2.5" Stainless Steel Brushes
- Window Squeegee with Bristles
- Multi Use Dispenser Bottle
- 2.5" and 5" Sink Drain tools
- Extended Length Nozzle
- Slim Nozzle Extension Tube
- 20' Flexible Hose
- Triangular, Rectangular & Diamond Pad Inserts
- Luxor Cart and Chrome Cart

#### **FEATURES**

- 3 Pressure Setting on Handle
- Total Electronic System
- Chemical Free, only uses tap water
- Variety of Attachments
- Low Pressure (65psi)
- Low Moisture (5%)
- High Temperature (220°F)
- User Friendly
- No MSDS Training and Administration
- Multiple Cleaning Applications
- Environmentally Friendly
- Affordable

## SPECIFICATIONS

VAPOR BLITZ I		
Control Handle	3 Speed (45-55-65psi)	
Voltage	115 & 220 Volts (60HZ)	
Current Draw	14.7 amps	
Weight	19 lbs.	
Stainless Steel Boiler	1 qt. w/Incoloy Element	
Water Reservoir Capacity	3 qts.	
Operating Time	4 hrs. per full tank	
Power	1700 Watts	
Steam Production	8 lbs.	
Max. Temp. Boiler	290°F	
Temp. at Tip	220°F	
Сар	Non-pressurized	

STEAMAX		
Control Handle	3 Speed (45-55-65 psi)	
Voltage	115 Volts (60HZ)	
Current Draw	14.7 amps	
Weight	14 lbs.	
Stainless Steel Boiler	2.4 qts. w/Incoloy Element	
Water Reservoir Capacity	N/A	
Operating Time	2 hrs. per full tank	
Power	1700 Watts	
Steam Production	8 lbs.	
Max. Temp. Boiler	290°F	
Temp. at Tip	220°F	
Cap	Pressurized	

VAPOR BLITZ II		
Control Handle	3 Speed (45-55-65psi)	
Voltage	115 & 220 Volts (60HZ)	
Current Draw	14.7 amps	
Weight	15 lbs.	
Stainless Steel Boiler	2.64 qt. w/Incoloy Element	
Water Reservoir Capacity	N/A	
Operating Time	2.5 hrs. per full tank	
Power	1700 Watts	
Steam Production	8 lbs.	
Max. Temp. Boiler	290°F	
Temp. at Tip	220°F	
Сар	Pressurized	

3.3 KW		
Power Consumption	3.3 KW / 15amps	
Steam Production	8.4 lbs./hr.	
AISI 304 Stainless Boiler	1.5 quarts	
Tank Capacity	1.25 gal.	
Detergent Tank Capacity	1.25 gal.	
Machine Size	24" x 14" x 39"	
Net Weight	66 lbs.	
Voltage	208/220V-60HZ (single phase)	
Working Pressure (up to)	Up to 150 psi adjustable	
Working Hours per Day	24 / 7	
Boiler Temperature (max.)	325° F	

Warranty — Two years on stainless steel boiler and 90 days on electronics.