



Instructions for use

RodentStop: Animal-friendly barrier paste

RodentStop is used to seal seams, cracks and holes in order to prevent ingress from rodents and other pests. RodentStop qualifies for exemption from registration under the Federal Insecticide, Fungicide and Rodenticide Act.

RodentStop applications include:

- Cracks, joints and holes in brickwork.
- Joints and expansion joints.
- Steel, cast-iron and PVC recesses and ducts.
- Settlement cracks.
- Connections between brickwork and drains.
- Sewer connections
- Ducts for (electrical) cables
- Gnawed openings

Advantages of RodentStop:

- Ready-to-use
- Contains no pesticides
- Instantly waterproof (suitable for indoor & outdoor application)
- Instantly active barrier
- Sustainable
- IPM compliant
- Paintable
- Installation possible in cold and warm conditions (-50°F / 170°F) [-45°C / 75°C]
- Metal reinforced and metal detectable
- Exempt from FIFRA registration

Industries

RodentStops unique properties allow the barrier paste to be used on a wide scale in the food industry as prescribed in the specifications.

RodentStop can be also be used in kitchens, bakeries, distribution centres, manufacturing facilities and companies with hygiene sensitive areas and environmental requirements.

Composition

Blend of vegetable oils, fillers, EPS beads and metal fibers.

Packing

RodentStop is packaged in 340 g (± 12 oz) standard caulking tube cartridges.

A box contains 12 cartridges of 300 ml each.



Instructions

Preparation

Make sure the surface is clean and dry.
Remove any loose material.

Application

- 1 Cut off the tip of the cartridge and screw on the applicator nozzle
- 2 Cut the applicator nozzle to a desired size depending on the size of the gap
- 3 Place the cartridge into a standard caulking gun
- 4 Slowly pull the caulking gun trigger. Apply evenly around the edges and fill the entire gap or opening
- 5 Smooth with a palette knife if desired
- 6 The barrier is now active
- 7 Clean hands and tools with a dry cloth after use, if necessary use mineral spirits.

Please note

- Keep out of reach of children
- Avoid contact with eyes and mouth
- Not suitable for consumption
- Can be used for openings/ducts of at least 1/4 inch (6 mm).
- Make sure the layer depth is at least 3/4 of an inch (18 mm).
- Do not apply near or around sources of heat
- Can be painted after 48 hours (at 70°F / 21°C)
- Surface is dry after 48 hours (at 70°F / 21°C)
- Store in a frost-free place
- Required layer depth may vary
- Waste resulting from the use of this product may be disposed of on-site or at an approved waste disposal facility





Precautionary Statements

To the best of our knowledge, RodentStop is not considered to be hazardous under the OSHA HazCom 2012 regulations or the Federal Hazardous Substances Act, for consumer products.



RodentStop™ is a trademark of PelGar International Ltd.

Important notice & Warranty

To the extent consistent with applicable law, PelGar International Ltd. warrants that this product will be free from defects in material and manufacturing for 90 days from the date of purchase from an authorized distributor. In that case, the product is reasonably fit when used in accordance with the directions for use.

This warranty does not extend to the use of RodentStop in a manner inconsistent with its labeling or when used under abnormal conditions. Many factors beyond the control of the manufacturer and/or uniquely within the user's knowledge and control can affect the use and performance of RodentStop in a particular application. Given the variety of factors that can affect the use and performance of RodentStop, the applicator is solely responsible for evaluating RodentStop and determining whether it is fit for a particular purpose and suitable for the user's method of application. All such risks shall be assumed by the user.



Manufactured for PelGar International Ltd.

PelGar USA
215 Evergreen Ct.
Saylorsburg, PA 18353
www.pelgar-usa.com

PelGar Asia Pacific
Level 22, 69 Ann St.
Brisbane, QLD 4000
www.pelgar.asia

From the makers of:

