



# Safety Data Sheet

**Date of Issue:** May 27, 2015

**Revision #:** 1

**Page:** 1 of 6

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Names:** MaxPar® G2-55, MaxPar® G2-60, MaxPar® G2-70, MaxPar® G2-80, MaxPar® G2-90  
MaxPar® G2-100

**Synonyms:** MaxPar G2 Base Oils, Lubricant Oils  
**General Uses:** Process Oil, Base Oil, Carrier, Lubricants  
**Chemical Family:** Petroleum Hydrocarbon, Hydro-treated Distillate  
**Responsible Party:**

Resolute Oil, LLC  
2951 Marina Bay Drive, Suite 130-334  
League City, TX 77573  
281-768-4509  
[www.resoluteoil.com](http://www.resoluteoil.com)

### Emergency Overview

#### 24 Hour Emergency Telephone Numbers:

Spill, Leak, Fire or Accident Call CHEMTREC:  
North America: (800) 424-9300  
Others: (703) 527-3887 (collect)  
California Poison Control System: (800) 356-3129

## 2. HAZARDS IDENTIFICATION

**GHS Classification** Aspiration Hazard Category – 1

### Label Elements

Hazard Symbols:



**Signal Word:** DANGER – Aspiration Hazard if it enters airways

**Hazard Statements:** H304 May be fatal if swallowed and enters airways.

### Precautionary Statements:

**Response:** If SWALLOWED: Immediately call a poison center or doctor/physician  
Do NOT induce vomiting  
Avoid breathing vapors. If inhaled, remove person to fresh air  
Wash thoroughly after handling

**Storage:** Store Locked up

**Disposal:** Dispose of contents / container to an approved waste disposal plant.

### Supplemental Information Hazard Statement:

2951 Marina Bay Drive, Suite 130-334, League City, TX 77573  
P 281-768-4509 F 713.864.3343



**Hazard Statement:** Static Accumulating material can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.  
**Prevention:** Keep away from heat/sparks/open flame/hot surfaces. No Smoking. Ground/Bond container and receiving equipment. These alone may be insufficient to remove static electricity.  
**Response:** Eliminate all ignition sources if safe to do so

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS #	Percent
Hydro-treated Distillate, Heavy Paraffin C20-C50	64742-54-7	0-100%
Hydro-treated Distillate, Light Paraffin C15-C30	64742-55-8	0-100%

**Composition Comments:** IP 346 <0.5% Polycyclic Aromatic Compound (PACs)

### 4. FIRST AID MEASURES

**Eye Contact:** If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention.  
**Skin Contact:** Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.  
**Inhalation (Breathing):** First aid is not normally required. If breathing difficulties develop, move away from source and seek medical attention.  
**Ingestion (Swallowing):** First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

**Most Important symptoms/effects, acute and delayed:**

EYES: May cause slight irritation, tears and a burning sensation  
SKIN: Causes mild irritation, potentially causing reddening, itching or inflammation  
INHALATION: Respiratory tract irritation may occur if exposed to fumes or mists  
INGESTION: Symptoms may include nausea, vomiting and diarrhea  
Aspiration into lungs may cause chemical pneumonia and lung damage.

**Medical Attention and Special Treatment needed:**

Treat symptomatically  
INGESTION: If ingested, this material represents a significant aspiration and chemical pneumonitis hazard. Vomiting is not recommended.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:** Dry chemicals, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

**Unsuitable Extinguishing Media:** Avoid solid water stream as it may scatter and spread fire.

**Special hazards arising from the substance or mixture:** Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposing products may include the following materials: Carbon Dioxide and Carbon Monoxide. Product is a static accumulating liquid. Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire. Static Electricity accumulation may be increased by the presence of small quantities of water or other contaminants. Restrict flow velocity to avoid build-up of static charge.

**Advice for firefighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as

2951 Marina Bay Drive, Suite 130-334, League City, TX 77573  
P 281-768-4509 F 713.864.3343



conditions warrant. Isolate immediate hazard area, keep unauthorized personnel out. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done with minimal risk.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate personal protective equipment to avoid direct contact. The material will burn, but will not ignite readily. Keep all ignition sources away from the spill/release.

**Environmental Precautions:** Stop spill/release if it can be done safely. Product is insoluble in water, so prevent it from entering drains or water ways. Notify appropriate state and local authorities.

**Method for clean up:** Use absorbent materials such as sand, earth or vermiculite on land spills. Use absorbent booms or skimming devices on water spills.

## 7. HANDLING AND STORAGE

**Handling:** Keep away from ignition sources. Be cautious of any drips or spills as product is extremely slippery. Do not enter confined spaces without appropriate equipment and procedures. Electrostatic charge may accumulate and create a hazardous condition when handling this material. Bond and Ground lines and equipment used during transfer to reduce the possibility of static spark-initiated fire.

**Storage:** Store containers in a clean, dry location, away from strong sunlight and heat or flames. Keep containers sealed when not in use. Empty containers retain residue and should be handled with care and disposed of properly.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	ACGIH	OSHA	Other
Hydrotreated Distillate, Heavy Paraffin C20-C50	5 mg/m TWA 10 mg/m STEL	5 mg/m	As Oil Mist, if generated 5mg/m TWA
Hydrotreated Distillate, Light Paraffin C15-C30	5 mg/m TWA 10 mg/m STEL	5 mg/m	As Oil Mist, if generated 5mg/m TWA

*STEL- Short Term Exposure Limit (15 minutes): TWA-Time Weighted Average*

### Appropriate Engineering Controls:

Consider the following when employing engineering controls and selecting personal protective equipment: Potential hazards of the material, applicable exposure limits, job activities and other substances in the work place.

If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

### Personal Protective Equipment (PPE):

**Respiratory:** If vapor or mist is generated by heating, spraying, etc, wear an air purifying respirator with mist filter. No special respiratory protection is normally required.

**Skin:** Wear gloves and long sleeve clothing to minimize contact.

**Eye/Face:** Wear glasses with side shield or goggles in case of splashing

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Liquid, Light yellow to Water White
<b>Odor:</b>	None to very mild petroleum
<b>pH</b>	N/A
<b>Melting/Freezing Point:</b>	< 10°F
<b>Initial Boiling Point:</b>	(SEE PRODUCT BULLETINS FOR SPECIFICS)

2951 Marina Bay Drive, Suite 130-334, League City, TX 77573  
P 281-768-4509 F 713.864.3343



<b>Flash Point:</b>	>320°F / 177°C (SEE PRODUCT BULLETINS FOR SPECIFICS)
<b>Test Method:</b>	Cleveland Open Cup (COC), ASTM D92
<b>Evaporation Rate:</b>	Not Applicable
<b>Flammability (solid, gas)</b>	Not Applicable
<b>LEL (vol % in air):</b>	No data
<b>UEL (vol % in air):</b>	No data
<b>Vapor Pressure (mm Hg):</b>	<1
<b>Vapor Density (air=1):</b>	>1
<b>Specific Gravity:</b>	0.82 – 0.88 (SEE PRODUCT BULLETINS FOR SPECIFICS)
<b>Solubility in Water:</b>	Insoluble
<b>Partition coefficient:</b>	log POW: >6 This product is soluble in oil
<b>Auto-ignition Temperature:</b>	No data
<b>Decomposition Temperature:</b>	No data
<b>Viscosity:</b>	50 – 135 SUS @100°F (SEE PRODUCT BULLETINS FOR SPECIFICS)

**Note:** Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm).

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Not chemically reactive
<b>Chemical Stability:</b>	Stable under normal ambient and anticipated conditions of use
<b>Possibility of hazardous reactions:</b>	Not anticipated under normal conditions
<b>Conditions to Avoid:</b>	Extended exposure to high temperatures can cause decomposition.
<b>Materials to Avoid (Incompatible Materials):</b>	Avoid contact with strong oxidizing agents.
<b>Hazardous Decomposition Products:</b>	Not anticipated under normal conditions

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure:

<b>Ingestion:</b>	Likely route of exposure
<b>Inhalation:</b>	Likely route of exposure
<b>Skin Contact:</b>	Likely route of exposure
<b>Eye Contact:</b>	Likely route of exposure

### Symptoms related to physical, chemical and toxicological characteristics:

**Inhalation:** Not expected to be a hazard for static vapor at ambient temperatures. Inhalation of mist or spray may be harmful and cause pulmonary edema or aspiration pneumonia. Oil deposits in the lung may lead to fibrosis and reduced pulmonary function.

**Skin Irritation:** May cause mild skin irritation, redness, itching and inflammation

**Eye Damage/Irritation:** May cause slight eye irritation, tears and a burning sensation

**Ingestions:** May cause gastrointestinal irritation, nausea, vomiting and diarrhea

### Information on toxicological effects:

Components	Species	Test Results
<b>Heavy Paraffinic Hydro-treated Distillate (CAS 64742-54-7)</b>		
<b>Light Paraffinic Hydro-treated Distillate (CAS 64742-55-8)</b>		

Dermal – LD50	Rat	>2000 mg/kg
Inhalation – LC50	Rat	>5 mg/kg
Oral – LD50	Rat	>5000 mg/kg

<b>Skin corrosion/irritation</b>	Not classified
<b>Serious eye damage/eye irritation</b>	Not classified
<b>Respiratory sensitization</b>	Not classified
<b>Skin sensitization</b>	Not classified
<b>Germ cell mutagenicity</b>	Not classified
<b>Carcinogenicity</b>	Not classified



**Reproductive toxicity**  
**Specific Target organ toxicity**  
**Aspiration toxicity**  
**Toxicological data**

IP 346 < 3.0% - Polycyclic Aromatic Compounds as measured by IP 346 method  
 Not classified  
 Not classified  
 Not classified  
 Mineral Oil mists from highly refined or hydro-treated oils are generally of low acute and sub-chronic toxicity. Overexposure to mists may cause inflammation of the lungs and lipid pneumonia.

## 12. ECOLOGICAL INFORMATION

**Eco-toxicity** Not classified in terms of eco-toxicity

Components	Species	Test Results
<b>Heavy Paraffinic Hydrotreated Distillate (CAS 64742-54-7)</b>		
<b>Light Paraffinic Hydro-treated Distillate (CAS 64742-55-8)</b>		
<i>Acute</i>		
Algae – EC50	Algae	> 1000 mg/l, 96 hr
Crustacea – EC50	Daphnia magna	>100 mg/l, 48 hr
Fish – LC 50	Fish	> 1000 mg/l
<i>Chronic</i>		
Crustacea – NOEL	Daphnia magna	1000 mg/l, 21 d
<b>Persistence and degradability</b>	Not readily biodegradable	
<b>Bio-accumulative potential</b>	May bio-accumulate in aquatic organisms	
<b>Partition coefficient n-octanol/water (log Kow)</b>		
Heavy Paraffinic Hydro-treated Distillate (CAS 64742-54-7)		>4
Light Paraffinic Hydro-treated Distillate (CAS 64742-55-8)		>4
<b>Mobility in soil</b>	May partition into air, soil and water	
<b>Other adverse effects</b>	No other adverse effects expected	

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with appropriate local, state and federal regulations.  
 Empty drums/containers should be sealed and returned to a re-conditioner.

## 14. TRANSPORTATION INFORMATION

### DOT - U.S. Department of Transportation

**Shipping Description:** Not regulated.

**Trucking Freight description:** 65 Petroleum Oil, N.O.I.B.N

**Note:** The provisions of 49 CFR, Part 130 apply for shipments over 3,500 bulk gallons, requiring carrier emergency plans for spills and accidents.

### IATA – Int’l Air Transport Association

Not Regulated

### IMDG – Int’l Maritime Dangerous Goods

Not Regulated

### Annex II of MARPOL 73/78 and the IBC Code:

Not classified for MARPOL.

## 15. REGULATORY INFORMATION

2951 Marina Bay Drive, Suite 130-334, League City, TX 77573  
 P 281-768-4509 F 713.864.3343



**U.S. Regulations:**

**CERCLA/SARA - Section 311/312 (Title III Hazard Categories)**

**Acute Health:** Yes  
**Chronic Health:** No  
**Fire Hazard:** No  
**Pressure Hazard:** No  
**Reactive Hazard:** No

**CERCLA/SARA - Section 313 and 40 CFR 372:**

This material does not contain toxic chemicals (in excess of the applicable de minimis concentration) that are subject to the reporting requirements of SARA 313 (40 CFR 372):

**EPA (CERCLA) Reportable Quantity (in pounds):** --None Known--

**CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds):**

This material does not contain extremely hazardous substances subject to the reporting requirements of SARA 302 (40 CFR 372)

**California Proposition 65:**

This material does not contain any component or chemical currently known to the State of California to cause cancer, birth defects or other reproductive harm at levels which are subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5)

**Carcinogen Identification:**

This material has not been identified as a carcinogen by NTP, IARC, or OSHA. See Section 11 for carcinogenicity information of individual components, if any.

**TSCA:** All components are listed on the TSCA inventory, or not required to be listed on the TSCA inventory.

**International Regulations:**

**Canadian Regulations:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**Domestic Substances List:** Listed

**WHMIS Hazard Class:** Not Regulated

**International Inventories:**

This material is listed on the following inventories:

Australia (AICS)  
Canada (DSL)  
China (IECSC)  
Europe (EINECS)  
Japan (ENCS)  
Korea (ECL)  
New Zealand  
Philippines (PICCS)

## 16. OTHER INFORMATION

**Disclaimer of Expressed and implied Warranties:**

The information presented in this Material Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license

Date of issue: May 27, 2015

Previous issue date: March 1, 2015

Basis for revision: Updated data

2951 Marina Bay Drive, Suite 130-334, League City, TX 77573  
P 281-768-4509 F 713.864.3343