



StealthNet®

WHERE TO USE

Any enclosed or semi-enclosed area, opening or configuration where pest birds are to be excluded, including open beam structures, loading docks, buildings façades, courtyards, bridges, etc.

TARGET BIRD

All species

BIRD PRESSURE

Heavy

MATERIAL


Polyethylene twine and stainless steel installation hardware

INSTALLATION

Netting attached to pre-installed cable system

INSTALLATION LEVEL

Involved



Installation video at
www.birdbarrier.tv



A Certified Installer secures StealthNet over a hospital's HVAC system to exclude birds.



StealthNet installed under beams and other perches at a shopping center.



StealthNet being installed between two buildings to keep pigeons away from sensitive equipment.

Almost Invisible

StealthNet is available in black, stone (beige) and white. The netting is composed of very thin, ultra-strong, knotted strands of polyethylene twine.

Long-Lasting

StealthNet is manufactured using the most advanced technology in the world, and has been developed to withstand a wide range of environmental conditions. Polyethylene is the most ultra-violet resistant netting material available and StealthNet has extra U.V. stabilizers added in its raw materials, creating a durable, long-lasting net.

Installation

StealthNet can be installed using a variety of fasteners created specifically for your building's needs. Whether it's masonry, steel or wood, we offer a discrete suspension system for a maintenance-free permanent installation.

Totally Humane

StealthNet provides a harmless, impenetrable barrier against all pest birds.

The Benefits of StealthNet

Six strands of polyethylene, each 12/1000 in. (hence the name 12/6), are wrapped rope-like into one strong, rot-resistant, U.V. protected twine. With a breaking strength of 52 lbs. per twisted strand, StealthNet is the strongest polyethylene netting available in the world.

StealthNet's U.V.-treatment and color pigmentation are embedded in the composition (not just dipped), making the net more resistant to the effects of the sun with a more consistent coloring throughout.

Benefits

- » Effective against all bird species
- » Highly resistant to ultraviolet rays
- » Flame-resistant (also available flame-proof, pg. 8)
- » Available in a variety of colors
- » Available in 7 standard and cut to your custom sizes
- » Nearly invisible in most situations
- » Low-profile installation system
- » Twine is twisted and knotted
- » Will not rot or absorb water
- » Protecting structures worldwide
- » Specified on historical properties

Warranty

Black StealthNet: **10 years**
Stone & White StealthNet: 3 years
Extended warranties for indoor applications are available.
See page 9 for more details.



StealthNet®



Four sizes of StealthNet offer complete exclusion

2 in. Mesh

Pigeons and larger birds



10-year warranty
on Black StealthNet


1-1/8 in. Mesh

Starlings, grackles, blackbirds, etc.




3/4 in. Mesh

Sparrows, swallows & other small birds



Use Standard netting for jobs under 25' x 25'.
Use Heavy Duty nets for larger jobs.

StealthNet Colors




White Stone Black

4 in. Mesh

For gulls and other aquatic birds. It is generally installed horizontally over roofs and bodies of water.

Installation of Nets

StealthNet is attached to a 5/64-inch (2mm) perimeter cable which is supported by a wide variety of intermediate and corner attachments designed for masonry, wood or steel. The cable is tensioned using turnbuckles and the netting is attached to the cable using net rings.



| SIZES | 25' x 25' | 25' x 50' | 25' x 75' | 50' x 50' | 50' x 75' | 50' x 100' | 100' x 100' |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| 3/4" Standard | | | | | | | |
| Black | N1-B110 645088 | N1-B120 645089 | N1-B130 645090 | N1-B220 645091 | N1-B230 645092 | N1-B240 645093 | N1-B310 |
| Stone | N1-S110 645095 | N1-S120 645096 | N1-S130 | N1-S220 | N1-S230 | N1-S240 645101 | N1-S310 |
| 3/4" Heavy Duty | | | | | | | |
| Black | N1X-B110 638013 | N1X-B120 638014 | N1X-B130 638015 | N1X-B220 638016 | N1X-B230 638017 | N1X-B240 638018 | N1X-B310 613947 |
| Stone | N1X-S110 638020 | N1X-S120 638021 | N1X-S130 638022 | N1X-S220 | N1X-S230 | N1X-S240 | N1X-S310 |
| White | N1X-T110 650684 | N1X-T120 650685 | N1X-T130 | N1X-T220 650689 | N1X-T230 | N1X-T240 | N1X-T310 |
| 1-1/8" | | | | | | | |
| Black | N2-B110 636458 | N2-B120 637919 | N2-B130 668364 | N2-B220 | N2-B230 639159 | | N2-B310 645074 |
| Stone | N2-S110 | N2-S120 | N2-S130 | N2-S220 | N2-S230 | N2-S240 | N2-S310 |
| 2" | | | | | | | |
| Black | N3-B110 638033 | N3-B120 638034 | N3-B130 637925 | N3-B220 638035 | N3-B230 638036 | N3-B240 638037 | N3-B310 672774 |
| Stone | N3-S110 638039 | N3-S120 638040 | N3-S130 638041 | N3-S220 | N3-S230 | N3-S240 638044 | N3-S310 |
| White | N3-T110 | N3-T120 | N3-T130 | N3-T220 | N3-T230 | N3-T240 | N3-T310 |
| 4" | | | | | | | |
| Black | | | | | | N4-B240 672999 | N4-B310 676597 |

Nets in stock up to 100' x 200' - Ask your representative for more details.



StealthNet®

Custom-Cut Nets • No-Flame Net • Bat Net

Custom-Cut Nets

Custom-cut nets are available with no minimum cutting fee. The cutting fee is included in the price per square foot.



| | | |
|-----------------------------------|----------|------------------------|
| 3/4" Black StealthNet Std. Custom | N1-BCUS | 645094 |
| 3/4" Stone StealthNet Std. Custom | N1-SCUS | 645102 |
| 3/4" Black StealthNet H.D. Custom | N1X-BCUS | 638019 |
| 3/4" Stone StealthNet H.D. Custom | N1X-SCUS | 638026 |
| 3/4" White StealthNet H.D. Custom | N1X-TCUS | 650695 |
| 1-1/8" Black StealthNet Custom | N2-BCUS | 638031 |
| 1-1/8" Stone StealthNet Custom | N2-SCUS | 638032 |
| 2" Black StealthNet Custom | N3-BCUS | 638038 |
| 2" StealthNet Stone Custom | N3-SCUS | 638045 |
| 2" White StealthNet Custom | N3-TCUS | |
| 4" Black StealthNet Custom | N4-BCUS | |

*Custom prices are per square foot

Bat Net & Metal Mesh



Special knotted netting just for bats. Our 3/8" polyethylene knotted mesh is ideal for all bat species, and is far stronger than other nets available. The black mono-filament withstands ultraviolet radiation extremely well, and is very hard to see when installed in shadowed areas. Another great feature is the large sizes available so any bat exclusion is possible with a single sheet, eliminating the need for seams.

| | | |
|-------------------------------|---------|------------------------|
| StealthNet for Bats 10' x 10' | N8-B100 | 690645 |
| StealthNet for Bats 10' x 25' | N8-B105 | 672990 |
| StealthNet for Bats 25' x 25' | N8-B110 | 645218 |
| StealthNet for Bats 25' x 50' | N8-B120 | 639873 |
| StealthNet for Bats 50' x 50' | N8-B220 | 639872 |

Stainless Steel Wire Cloth

This high quality stainless steel hardware cloth is meant for difficult Bat exclusion projects. The mesh is on 1/2" centers and offers an effective long lasting exclusion screen where other products might fail. Four feet wide, this mesh available custom cut in 1 foot increments (min. order 4 sq. ft.) and is cut to your order. Lengths up to 100' long are available in a single piece. Please obtain delivery quotes for large orders.


| | | |
|-------------------------------|---------|------------------------|
| S.S. Wire Cloth (per sq. ft.) | N8-SS50 | 645195 |
|-------------------------------|---------|------------------------|



No-Flame StealthNet

Bird Barrier's No-Flame StealthNet conforms to NFPA 701, which states that the net is self extinguishing (it will put itself out after being exposed to an open flame). This net is ideal for interior applications like airplane hangars, sports facilities and other sensitive areas. It is also ideal for netting jobs around residential settings, like condos and apartment buildings. The No-Flame StealthNet is distinguished by a blue strand twisted in with the black strands.

| | | |
|-----------------------------------|----------|------------------------|
| 3/4" Black Flame-Proof 25' x 25' | N1F-B110 | 645212 |
| 3/4" Black Flame-Proof 50' x 50' | N1F-B220 | |
| 3/4" Black Flame-Proof 50' x 100' | N1F-B240 | |





- Ideal for:
- » Condos/Apartments
 - » Hotels
 - » Aircraft Hangars
 - » Warehouses
 - » All sensitive applications

Conforms to NFPA 701
Demand the Blue Strand!

PVC-Coated Galvanized Mesh

Black PVC coated 1/2" wire mesh offers an effective long lasting exclusion screen where other products might fail. Four feet wide this mesh is available in customs cuts in 1 foot increments. Also available in two standard rolls 6" x 100' and 12' x 100' for larger jobs. It can be bent into custom shapes and glued or screwed in place.

| | | |
|---------------------|---------|------------------------|
| 4' Wide, by sq. ft. | N8-PV05 | |
| 8" x 25' Roll | SP-EX50 | |
| 8" x 50' Roll | SP-EX55 | |
| 6" x 100' Roll | N8-PV10 | 798873 |
| 12" x 100' Roll | N8-PV15 | 802971 |



NEW! - Solar Panel Exclusion Kits. See page 25



StealthNet®

BirdBarrier


Hand Net Ring Tool

The standard tool for attaching netting to cable, it accepts a cartridge of 50 net rings for fast and easy use.

- Great for small jobs
- Light (0.5 lbs.)
- Affordable (relative to the other tools)
- Very maneuverable
- Fast and easy to re-load

| | | |
|-------------------------|---------|------------------------|
| Net Ring Tool | TH-1000 | 636543 |
| Galv. Net Rings (2,500) | TH-G100 | 636545 |
| S.S. Net Rings (2,500) | TH-S100 | 638175 |



Stanley "Ringer" Net Ring Tool

Stanley "Ringer" uses a 9/16" net ring and has a handle like grip that helps eliminate hand, wrist and forearm fatigue when the job requires a lot of net rings.

| | | |
|--------------------------------|---------|------------------------|
| Net Ring Tool, 9/16" Net Rings | TH-1500 | 805080 |
| 9/16" Galv. Net Rings (2,500) | TH-G150 | 805081 |
| 9/16" S.S. Net Rings (2,500) | TH-S150 | |



A Bird Barrier Certified Installer installs horizontal StealthNet under this theatre overhang to keep sparrows from perching on the beams and pipes over the stage.

Net rings hold the netting to the cable and are applied using one of four tools. Each tool has distinct features; most professionals have at least two of the following tools in their tool box.



Net ring tools make small, metal loops that connect netting together, or hold netting to the cable.

Stanley Pneumatic Net Ring Tool

These fast operating tools are a must on large netting projects. They will save you time and money. They run off a compressor and hold 100 rings and uses the 1/2-inch ring size. Pneumatic rings are packed in 10,000 rings/box. Requires a 95 PSI-capable compressor.

- Fast and reliable
- Agile nose gets into tight spaces
- Holds 100 rings
- 2.8 lbs.

| | | |
|--------------------------------|---------|------------------------|
| Net Ring Tool, 1/2" Net Rings | TH-2000 | 655503 |
| 1/2" Galvanized Rings (10,000) | TH-G200 | 655504 |
| 1/2" S.S. Rings (10,000) | TH-S200 | 655505 |
| 3/4" Galvanized Rings (10,000) | TH-G300 | 680518 |
| 3/4" S.S. Rings (10,000) | TH-S300 | 680520 |



Cordless Net Rings

| | | |
|-------------------------------|---------|------------------------|
| Galvanized Net Rings (10,000) | TH-G400 | 733845 |
| Stainless Net Rings (10,000) | TH-S400 | 639858 |
| Black Net Rings (12,000) | TH-B400 | 661764 |



Tool Discontinued

EMPLOYEE PROFILE » TONY



"Call me with any questions regarding your bird project. I'm here to make sure you get exactly what you need to make a sale or complete your project. I'm in the office at 6 a.m. PST. I look forward to hearing from you."



Selecting the Right Turnbuckle

The cable must be tensioned properly to insure a secure installation. Use small turnbuckle for cable runs under 25 ft., medium turnbuckle for runs 25 to 75 ft., and large turnbuckle for runs over 75 ft.

Galvanized Turnbuckles

Use galvanized for dry, salt-free climates with galvanized net rings and net cable. 10 per pack.

| | | |
|---------------------------|---------|------------------------|
| Sm. Turnbuckle Galv. (10) | NT-G100 | 638181 |
| Med. Turnbuckle Galv.(10) | NT-G200 | 639864 |
| Lg. Turnbuckle Galv. (10) | NT-G300 | 638182 |



Stainless Steel Turnbuckles

Stainless steel is best for wet or salty climates. Use with stainless steel cable and net rings. 10 per pack.

| | | |
|---------------------------|---------|------------------------|
| Sm. Turnbuckle S.S. (10) | NT-S100 | 638183 |
| Med. Turnbuckle S.S. (10) | NT-S200 | 638184 |
| Lg. Turnbuckle S.S. (10) | NT-S300 | 645236 |



Net Cable

Our 5/64" (2mm) diameter 7x7 construction cable is the standard for perimeter support. It is available in galvanized or stainless steel. Stainless steel is recommended for installations near heavy moisture, chemical environs or salt-laden air.

| | | |
|--------------------------|---------|------------------------|
| Net Cable Galv. (250 ft) | NC-G250 | 638057 |
| Net Cable Galv. (500 ft) | NC-G500 | 638058 |
| Net Cable S.S. (250 ft) | NC-S250 | 638059 |
| Net Cable S.S. (500 ft) | NC-S500 | 638060 |



Cable Cutter

The sharpest, longest-lasting and easiest tool to use for cutting heavy-duty cable. The overlapping heads give a clean cut up to 5/32" (4mm). The tool features a spring loaded rubber grip handle and a security locking latch.

| | | |
|--------------------|---------|------------------------|
| Cable Cutter (ea.) | TO-CC10 | 639843 |
|--------------------|---------|------------------------|



Heavy Duty Installation

Heavy duty cable and ferrules **should be used on oversized or extra-heavy applications only**. If heavy forces from wind or snow are anticipated this heavy duty hardware should be considered. Call our offices for more information.

Heavy Duty Net Cable

This 5/32-inch cable should be used where extra strength is desired such as where StealthNet not supported for runs of 100 feet or more.

| | | |
|---------------------------|---------|------------------------|
| Galvanized (500 ft.) | NC-G532 | 675380 |
| Stainless Steel (500 ft.) | NC-S532 | 675378 |



Heavy Duty Ferrules

These ferrules are to be used with the heavy duty net cable. Use two per end/loop end and crimp twice per Ferrule. 100 per pack.

| | | |
|--------------------|---------|------------------------|
| 5/32-inch Ferrules | NC-N500 | 674213 |
|--------------------|---------|------------------------|



Heavy Duty Eye Bolt

When adding extra tension to heavier cable it's important to use a corner anchor that will not bend or break.

| | | |
|--------------------------|---------|------------------------|
| Heavy Duty Eye Bolt (10) | NB-EB30 | 674214 |
|--------------------------|---------|------------------------|



Heavy Duty Crimper

Use this tool with heavy duty ferrules.


| | | |
|------------|---------|------------------------|
| Crimp Tool | TN-R300 | 674223 |
|------------|---------|------------------------|





The Importance of Corner Attachments

The most important part of a netting job is the corners (where the cables end or turn corners) due to the tension applied by the turnbuckles and the weight of the net. Strong cable-ends and corners are achieved using the correct selection from a wide variety of anchoring systems enabling you to secure the system to any substrate.



Netbolts - Galvanized

This high-load bearing expansion bolt is the perfect anchor for most masonry, stone or concrete corner/end attachments. Use the smaller M6 for cable runs under 100' and the larger M8 for runs over 100'. 10 per pack.

| | | |
|-------------------------|---------|------------------------|
| Netbolt M8 Galv. (10) | NB-M8G0 | 636420 |
| 12mm Drill Bit (for M6) | TB-S120 | 639875 |
| Netbolt M6 Galv. (10) | NB-M6G0 | 636419 |
| 14mm Drill Bit (for M8) | TB-S140 | 639874 |



Netbolts - Stainless Steel

High grade stainless steel expansion bolt for masonry, concrete or stone. 10 per pack.

| | | |
|----------------------|---------|------------------------|
| Netbolt M6 S.S. (10) | NB-M6S0 | 636410 |
| 10mm Drill Bit | TB-S100 | 639876 |



Eye Bolt with Nut

Corner/end attachment for an I-beam or other thick metal.

| | | |
|-----------------------|---------|------------------------|
| Eye Bolt - Galv. (20) | NB-EB10 | 645106 |
| Eye Bolt - S.S. (10) | NB-EB20 | 645281 |



Screw Eyes - Heavy Duty

Ideal for cable ends and corners when anchoring in wood.

| | | |
|--------------------------|---------|------------------------|
| Screw Eye H.D. Galv (50) | NB-SE10 | 638053 |
| Screw Eye H.D. SS (20) | NB-SE20 | 645107 |




Ideal as Corner & Intermediate Attachments

Multi-Purpose Cable Brackets

These versatile stainless steel bracket can be used as a corner or intermediate attachment, and installed as a permanent fixture or as a quick-release cable holder. 100 per pack.

| | | |
|--------------------------|---------|------------------------|
| A) With Hilti Pin | NI-CB15 | 645398 |
| B) Bracket w/13/64" Hole | NI-CB10 | 645233 |
| C) Bracket w/1/4" Hole | NI-CB25 | 799870 |



Talk to an Expert. We will help you succeed: 800-503-5444.

Mini Netbolts

Corner attachment for smaller net jobs (cable runs under 25 feet). Drill an 8mm hole, insert the bolt and turn the eye for a solid hold. Zinc passivated or stainless steel. 10 per pack.

| | | |
|--------------------------|----------|------------------------|
| Mini Netbolt Galv. (10) | NB-MBG10 | 654753 |
| Mini Netbolt S.S. (10) | NB-MBS10 | 672972 |
| 8mm Drill Bit (for both) | TB-S080 | 639877 |



Metal-Hit Anchor

Use this anchor to attach multi-purpose brackets to concrete, brick or cement block. Hitting the pin with a hammer locks the part in place. 100 per pack.

| | | |
|------------------------|---------|------------------------|
| Metal-Hit Anchor (100) | NI-SP02 | 645197 |
| 4.8mm Drill Bit | TB-S048 | 639880 |



Girder Clamp

For steel up to 2" thick. Bolt on an I-beam or flat steel and attach your cable or turnbuckle directly to it. 10 per pack.

| | | |
|--------------------------|---------|------------------------|
| Girder Clamp - S.S. (10) | NB-GC00 | 638065 |
|--------------------------|---------|------------------------|



Heavy Duty Steel Clamp

This clamp defines the term "heavy duty." Your best bet for larger net installations, this clamp can hold up to 630 lbs. of tensioned weight. Bolt to an I-beam or other steel structure and run your cable inside the jaws. Opens up to 2". 4 per pack.

| | | |
|----------------------|---------|------------------------|
| H.D. Steel Clamp (4) | NB-GC10 | 672971 |
|----------------------|---------|------------------------|



Drill bits, glue, glue-guns, screws, pins, tools, see p. 23



Hilti .27 Shot

Hilti's powder-actuated tools are powered by easy-to-use shot cartridges. Simply insert the cartridge up through the bottom of the tool, and they are in place and ready to go. Bird Barrier carries the heavy charge (red) because the tool is adjustable and can be backed down to much less power if necessary. Ten shots per strip, 100 shots per pack.

| | | |
|------------|---------|------------------------|
| Hilti Shot | T0-H250 | 672932 |
|------------|---------|------------------------|





The Importance of Intermediate Attachments

Intermediate attachments hold cable against the wall between corner attachments.

We recommend:

- 2" netting = one every 2-3 feet
- 1-1/8" netting = one every 2 feet
- 3/4" netting = one every 1.5 feet



Multi-Purpose Cable Bracket

This versatile stainless steel bracket can be used as a corner or intermediate attachment, and installed as a permanent fixture or as a quick-release cable holder.

| | | |
|--------------------------|---------|--------|
| A) With Hilti Pin | NI-CB15 | 645398 |
| B) Bracket w/13/64" Hole | NI-CB10 | 645233 |
| C) Bracket w/1/4" Hole | NI-CB25 | 799870 |



See photos of this in use on page 13.

Split Pins and Anchor Rivets

One of the strongest and most discreet intermediate attachment systems available for stone, masonry or brick. Insert the Anchor Rivet into a pre-drilled hole and hammer the Stainless Steel Split Pin home. Thread the cable through the hole in the Split Pin. Different lengths are available depending on the substrate integrity and use.

| | | |
|-------------------------|---------|------------------------------|
| Anchor Rivet 1" (100) | NI-AR10 | 638185 |
| Split Pin 1" (100) | NI-SP10 | 638209 |
| Anchor Rivet 1.5" (100) | NI-AR15 | 638186 |
| Split Pin 1.5" (100) | NI-SP15 | 638210 |
| 6.5mm Drill Bit | TB-S065 | 639878 (for both Split Pins) |



Net Spike

This hammer-in attachment is the strongest attachment available for stone, concrete or solid brick. Does not require a plastic anchor sleeve, the bent shaft holds it securely in place. Zinc or Stainless Steel coated.

| | | |
|----------------------------|---------|--------|
| Net Spike (100) | NI-SP00 | 636426 |
| Net Spike SS (100) | NI-SP05 | 638176 |
| 4.8mm Drill Bit (for both) | TB-S048 | 639880 |



Net Loop

Low profile, stainless steel intermediate attachment for wood or sheet metal. Secure with self tapping screw.

| | | |
|----------------|---------|--------|
| Net Loop (100) | NI-WC20 | 652266 |
|----------------|---------|--------|



Lag Screw

Screw directly into wood, or use with an anchor for masonry.

| | | |
|----------------------|---------|--------|
| Stainless, Sm. (100) | NI-NS10 | 652263 |
| Anchor, Sm. (100) | NI-NS12 | 652264 |
| Galvanized Lg. (100) | NI-NS25 | 652265 |



Lag Screw Driver

Drive our Lag screws into wood and plastic anchors with this tool that fits into the chuck of your hand drill.

| | | |
|------------------------|---------|--------|
| Lag Screw Driver (ea.) | TB-SP10 | 652267 |
|------------------------|---------|--------|

G

Girder Clips

This strong, hammer-on clip allows you to attach cable to hard-to-drill steel beams. Hammer the clip onto the edge of an I-Beam with the cable running through the jaws (not through the hole), and your cable is secure (see photo below, right). Available in Black Oxide which are not recommended for weather-exposed exterior use and Stainless Steel for all weather applications.



| | | |
|----------------------------|----------|--------|
| A) 3/32"-9/64" (100) | NI-GC10 | 638061 |
| B) 1/8"-1/4" (100) | NI-GC20 | 638062 |
| C) 5/16"-1/2" (100) | NI-GC30 | 638063 |
| D) 9/16"-3/4" (100) | NI-GC40 | 638064 |
| E) S.S. 1/8" - 1/4" (100) | NI-GCS20 | |
| F) S.S. 5/16" - 1/2" (100) | NI-GCS30 | 650760 |
| G) S.S. 9/16" - 3/4" (100) | NI-GCS40 | |

Hilti Loop - Open and Closed

Constructed of high quality, zinc-plated steel, the Hilti Loop is an easy-to-use attachment for stone, concrete and brick. Drill a hole and hammer it home. Open option for removable nets.



| | | |
|--------------------------|---------|--------|
| Hilti Closed Loop (100) | NI-H100 | 638050 |
| Hilti Open Loop (100) | NI-H200 | 638051 |
| 8mm Drill Bit (for both) | TB-S080 | 639877 |

Kwik Tog & Eye Loop (for Stucco)

Stucco is one of the most challenging substrates for bird control. This durable plastic attachment affords a solid base for the screw eye. Drill a 3/8" hole, insert the Kwik Tog so it expands behind the stucco.



| | | |
|--------------------------|---------|--------|
| Kwik Tog & Eye Loop (50) | NI-KT10 | 645232 |
|--------------------------|---------|--------|

Drywall Anchor

This clever anchor drills itself into Drywall with a Phillips head screw driver. Simply drive a screw into the anchor once it is set in place. Use to hold Multi-Purpose Bracket or net loop.



| | | |
|----------------------------|---------|--------|
| Metal Anchor w/Screw (100) | NI-SP01 | 645196 |
|----------------------------|---------|--------|



Thin Wire Net Clip

Great for small jobs, this stainless steel clip attaches netting to a structure without running cable. Not recommended for jobs over 5' x 5'.

| | | |
|--------------------------|---------|--------|
| Thin Wire Net Clip (100) | NI-WC10 | 645234 |
|--------------------------|---------|--------|

"S" Hook

Heavy duty stainless steel fastener can be secured with screws or fired-in pins.



| | | |
|--------------------------------|---------|--|
| "S" Hook Stainless Steel (100) | NI-WC30 | |
|--------------------------------|---------|--|



Drill bits, glue, glue-guns, screws, pins, tools, see p. 23



StealthNet®

Zippers & Magnets

BirdBarrier®

Screw Eyes (Small)

These screws for wood are very sturdy intermediate attachments.

| | | |
|-----------------------------|---------|--------|
| Screw Eye Small, Galv (100) | NI-SE10 | 638052 |
| Screw Eye Small, SS (20) | NI-SE20 | 645235 |



Screw Eye Driver

Fits in the chuck of your power drill and allows you to drive small and heavy duty screw eyes into wood fast and easy. Just get the eye started, slip the Driver over the loop and screw it in.

| | | |
|------------------------|---------|--------|
| Screw Eye Driver (ea.) | TB-SE10 | 645217 |
|------------------------|---------|--------|



Net Magnets

Net Magnets are new intermediate attachments for metal substrates. They are extremely quick to secure in place and can be useful for following contours of a metal substrate, with or without wire cable. Two models available. The magnet is not anywhere near as strong as an actual anchor drilled into the surface, so use caution when using these. Use for small sections of netting under little tension.

Light Duty Magnets exert 16 lbs. of force each. The inverted clips face each other so you can simply push the netting or cable into the opening. It's also easy to open the clip, for easy access.

| | | |
|-----------------------------|---------|--------|
| Light Duty Net Magnets (10) | NI-MG00 | 808760 |
|-----------------------------|---------|--------|




EMPLOYEE PROFILE » VINCE



"I'm part of the New Jersey operation for Bird Barrier. I love being out in the field and solving seemingly impossible bird control challenges for our customers. You'll also find me at industry events and training, and on occasion, tackling my fear of heights in a lift. You'll find me hopping around the world in my free time".

The Use of Net Zippers

StealthNet zippers can be installed to open netting for horizontal vertical access, using net rings.



Closed-End Zippers

Zippers can be net-ringed into the netting to create any sort of an opening. Heavy duty marine construction insures long-life. Zippers are now available up to 300 feet!

| | | |
|------------------------|---------|--------|
| 1' Black Zipper (ea.) | NZ-B100 | 639859 |
| 3' Black Zipper (ea.) | NZ-B300 | 639861 |
| 6' Black Zipper (ea.) | NZ-B600 | 639862 |
| Black Zipper (per ft.) | NZ-BCUS | 645239 |
| 1' Stone Zipper (ea.) | NZ-S100 | 654759 |
| 3' Stone Zipper (ea.) | NZ-S300 | 654761 |
| 6' Stone Zipper (ea.) | NZ-S600 | 654763 |
| Stone Zipper (per ft.) | NZ-SCUS | 654764 |
| 1' White Zipper (ea.) | NZ-W100 | |
| 3' White Zipper (ea.) | NZ-W300 | |
| 6' White Zipper (ea.) | NZ-W600 | |
| White Zipper (per ft.) | NZ-WCUS | |



Separating Zippers

Used to create a section of net that will fall open. Use this across the end of a trap door. Need a larger opening? Point the open end of the zipper at each other for a 16' opening.


| | | |
|-----------------|----------|--------|
| 8' Black Zipper | NZ-BS800 | 645221 |
| 8' Stone Zipper | NZ-SS800 | 675372 |
| 8' White Zipper | NZ-WS800 | |



Net Access Clips

Stainless steel net clips join pieces of netting to allow for removal of panels for access. New, thin design is hard to see.

| | | |
|-----------------------------|---------|--------|
| 2" Net Access Clips (100) | NZ-C200 | 655530 |
| 3/4" Net Access Clips (100) | NZ-C340 | 655531 |



StealthNet Repair Twine

Use for invisible seams and to make minor repairs.

| | | |
|------------------------|----------|--------|
| Black Net Twine (500') | NO-TWB10 | 674670 |
| Stone Net Twine (500') | NO-TWS10 | 674671 |
| White Net Twine (500') | NO-TWT10 | 674672 |



Net Scissors

A must on any netting job.

| | | |
|--------------------|---------|--------|
| Net Scissors (ea.) | TO-S100 | 645226 |
|--------------------|---------|--------|





HVAC Netting System

HVAC units provide birds with shelter (underneath the units), and a high perch to check out food and other opportunities (on top of the units).

Rooftop units can be difficult to protect. Installers generally screen off the bottoms, and put Daddi Long Legs on the top. The units need to be accessed for maintenance, and building owners generally don't like holes drilled in their roofs.


Our HVAC protection system offers many unique features:

- System protects top and space below the unit
- Corner Stand-off brackets raise net well above unit
- Brackets keep net away from the sides of the unit as well
- Brackets can usually mount to unit without screws
- Weighted hose secures to roof, no fasteners or holes necessary
- Hose can be lifted up for repair access
- Installed using most standard Bird Barrier items (StealthNet, cable, net-rings, tools etc.)
- Zippers can be installed for smaller access, or as pipes and other obstructions demand

Stand-off Bracket, 24"
Stand-off Bracket, 48"
Weighted Hose, 25 ft.

HV-S024 [168770](#)
HV-S048 [NR-WR25](#)
NR-WR25 [115440](#)

Bird Barrier provides an online HVAC Calculator that will generate a list of the materials you need and the cost for each.
www.birdbarrier.com



The telescopic support poles allow netting to be installed securely over the heads of workers and equipment.

Telescoping Support Poles

These poles can be used to build raised netting systems. The poles can be used to keep the center cable higher (like a tent), or to raise a whole net system above a flat roof, or a roof covered with HVAC equipment.

The top of the pole has four holes designed to accommodate both perimeter net cable and turnbuckles. This flexibility allows the pole to accommodate a wide range of possible installations. The bolts half-way-up the poles can be loosened to adjust the poles to the perfect height. By tensioning the cables equally in each direction, the flat base will simply sit in place. Protective neoprene pads insure no damage is done to the roof. Extend poles from 4.5 ft. to 8 ft. Each pole includes one protective pad.

Pole Cable Support, 4'5"-8' HV-P04 [731748](#)
Protective Pad HV-PAD12 [732729](#)



Gridwire®

Gridwire or polyethylene Fluorescent GridTwine (more visible to birds) can be suspended in various horizontal and vertical patterns to deter large aquatic birds. Grid spacings are site and species specific. You can protect lakes, parking lots, warehouse roofs, etc. from gulls, geese and other large aquatic birds.

| | | |
|--|---------|------------------------|
| 5/64" Copper Ferrules for Gridwire (100) | NC-N150 | 645108 |
| 5/64" Open Copper Ferrules (100) | GW-C100 | |
| Ratchet Crimping Tool | TN-R100 | 638178 |
| .77mm SS Gridwire 500 ft. | GW-WX77 | 651434 |
| .96mm SS Gridwire 500 ft. | GW-WX96 | 652272 |
| Fluorescent GridTwine w/SS, 1,000 ft. | GW-T100 | |
| Pole Cable Support (see above) | HV-P04 | 731748 |



Orange Gridwire with two strands of SS wire for added longevity.





Hardware



SDS Drill Bits - for Masonry

Drill Bit Used For

| Drill Bit | Used For | Part Number |
|-----------|-----------------------------|----------------|
| 4.8mm | Metal-Hit Anchor, Net Spike | TB-S048 639880 |
| 6.5mm | Split Pins, Anchor Rivets | TB-S065 639878 |
| 8mm | Hilti Loops, Mini Netbolts | TB-S080 639877 |
| 10mm | M6 Stainless Netbolt | TB-S100 639876 |
| 12mm | M6 Galvanized Netbolt | TB-S120 639875 |
| 14mm | M8 Galvanized Netbolt | TB-S140 639874 |




WARNING: Do not substitute US sizes

Hilti Pins

Fire into steel or concrete using the powder-actuated tool to secure various brackets. Use X-EDNI pin for thick steel (more than 1/2"), and X-DNI for thinner steel and masonry.

| | | |
|-----------------------------|---------|--------|
| A) Hilti Pin - X-DNI (100) | NI-H300 | 645227 |
| B) Hilti Pin - X-EDNI (100) | NI-H400 | |



Self Tapping Screws

Used to fasten Bird Barrier brackets and clips to different metals. Small screw uses 1/4" nut driver; large screw uses 5/16" nut driver (see below).

| | | |
|---------------------------------|---------|--------|
| 1/2" Galvanized (100) | HA-S100 | 639854 |
| 1/2" Stainless Steel (100) | HA-S120 | 652259 |
| 3/4" Galvanized (100) | HA-S200 | 645084 |
| 1-1/4 in. Galvanized H.D. (100) | HA-S220 | |
| 3/4 in. Stainless Steel (100) | HA-S240 | |
| 1-1/4 in. Stainless H.D. (100) | HA-S260 | |



Magnetic Nut Setters

Ideal for driving self-tapping screws with a cordless hand drill. Magnetic tip holds the screw in place while you start the hole.

| | | |
|------------------------------|---------|--------|
| Mag Nut Setter (1/4") (ea.) | TB-HX10 | 645215 |
| Mag Nut Setter (5/16") (ea.) | TB-HX20 | 645216 |



Stainless Steel Screw and Plastic Anchor

The best anchor for Coil clips, multi purpose cable attachment and many other Bird Barrier products.

| | | |
|----------------------------|---------|--------|
| Stainless Wood Screw (100) | HA-S300 | 645085 |
| Plastic Anchor (100) | NI-NS12 | 652264 |



Dripless Ergonomic Caulk Gun

Dripless? Absolutely! The flow of caulk stops when you stop. No thumb release, no buttons to push, no special way to click the handle. It's simple and automatic. Use for Bird Barrier Bond or Bird-Off Gel; either way you'll love how the bead stops when you release the handle.



Caulk Gun

TO-CG10 808539

Talk to an Expert. We will help you succeed: 800-503-5444.

Bird Barrier Bond

Green Tube - 5 Year Warranty

An exceptionally strong, flexible, adhesive. It handles dramatic temperature changes without cracking. Full cure is in 24 hours at normal temperatures.

- Securely holds metals and plastics to wood, steel, sheet metal, concrete, brick and most building substrates.
- Gray in color
- Excellent UV characteristics
- Cleanup is with soap and water. Apply wearing surgical gloves.
- Green - Moisture curable, solvent-free formula



New Bond 10.2 oz. (ea.)

HA-BB03 776954

E6100 - 1 Year Warranty

Strong, flexible, quick cure and ideal for interior applications out of the sun.

- Securely holds metals and plastics to wood, steel, sheet metal, concrete, brick and most building substrates.
- Clear in color



Original Bond 10.2 oz. (ea.)

HA-BB04 776732

Bond Guidelines

10.2 oz.

| | |
|-----------------------|-----------|
| BirdSlide | 25 feet |
| Bird-Flite | 35 feet |
| Birdwire Bases* | 125 bases |
| Coil Clips | 275 clips |
| DLL PVC Bases | 35 bases |
| Bird-Shock Flex-Track | 35 feet |

*Use Super Bond for Birdwire bases supporting end posts.



Buy Bond by the case and SAVE!

Bird Barrier Super Bond

Occasionally you can't wait for the regular bond to cure. Bird Barrier Super Bond cures in about one hour, so you can secure your products and be on your way. Requires Applicator & nozzles. 50 ml.

Super Bond Tube (2 part)

HA-BS01 639852

Super Bond Applicator (ea.)

HA-BS02 639856

Super Bond Nozzles (12)

HA-BS03 639855

Super Bond Guidelines

| | |
|----------------|----------|
| Bird-Flite | 8 feet |
| Birdwire Bases | 40 bases |
| Coil Clips | 60 clips |
| DLL PVC Bases | 10 bases |



Please Note: Bird Barrier Bond and Super Bond will not adequately adhere to nor is recommended for use with a fluoropolymer paint. This paint is marketed by some companies under the "Teflon", "Hylar", and "Kynar" brand names as coatings for anti-friction, anti-graffiti, etc. There is no warranty coverage for Bond applied to these surfaces.